UNDERGROUND INJECTION CONTROL PERMIT APPLICATION

Ute Tribal # 31-04 770' FNL & 703' FWL Sec. 31, T5S-R3W Duchesne County, Utah API # 43-013-32034

July 2015

Prepared for:
Bruce Suchomel

Groundwater Program, Mail Code 8P-W-UIC
U.S. Environmental Protection Agency
1595 Wynkoop St
Denver, CO 80202-1129

Prepared by:
Petroglyph Energy, INC.

960 Broadway Avenue, Suite 500, P.O. Box 70019
Boise, Idaho 83707
(208) 685-7600

FAX (208) 685-7605

TIER 1

UNDERGROUND INJECTION CONTROL PERMIT APPLICATION

O DEVIATION LOGS
O SUNDRY REPORTS.
O C BCS FOR AOR WER
OHOW WAS USDUNDED.

Ute Tribal # 31-04 770' FNL & 703' FWL Sec. 31, T5S-R3W Duchesne County, Utah API # 43-013-32034

July 2015

Prepared for:
Bruce Suchomel
Groundwater Program, Mail Code 8P-W-UIC
U.S. Environmental Protection Agency
1595 Wynkoop St
Denver, CO 80202-1129

Prepared by:
Petroglyph Energy, INC.

960 Broadway Avenue, Suite 500, P.O. Box 70019
Boise, Idaho 83707
(208) 685-7600

FAX (208) 685-7605

LIST OF ATTACHMENTS

Attachment No. 1 Area Topography Map

Attachment No. 2 Site Map

Attachment No. 3 Map of the A-Marker surface

Attachment No. 4 Cross-Sections of the injection formation

Attachment No. 5 Water Analysis

Attachment No. 6 Completion data for all wells in the AOR

Attachment No. 7 CBL for the UIC well

Attachment No. 8 Open hole log for the UIC well

Attachment No. 9 List of owners and Affidavit Notification

Attachment No. 10 Well bore diagrams for the UIC well

Attachment No. 11 P&A procedure

Attachment No. 12 MIT procedure

Attachment No. 13 Surety Bond letter

SUMMARY DOCUMENT UIC WELL APPLICATION Ute Tribal 31-04 API # 43-013-32034

The following document contains information provided in support of the application for the conversion of the Ute Tribal 31-04 well to an injection well in the Green River formation in the Antelope Creek Field in Duchesne County, Utah.

The Antelope Creek Field falls within the Uintah and Ouray Indian reservations and is within Indian Country; therefore, for facilities located on the reservation, only EPA-issued UIC permits are necessary for compliance with UIC regulations.

The EPA has issued an Area Permit #UT20736-00000 for the Underground Injection Control for the Antelope Creek Field. This area permit allows for additional producing wells to be converted to injection wells for enhanced recovery.

(1) Petroglyph Energy, Inc. (Petroglyph) is the operator and only working interest owner of wells located in the Antelope creek Field, Duchesne County, Utah. Petroglyph's business address is provided below:

Petroglyph Energy, Inc. 960 Broadway Avenue, Suite 500 P.O. Box 70019 Boise, ID 83707

- (2) Enclosed as Attachment No. 1 is a topographic map of a portion of the Antelope Creek Field, identifying all wells located in this area. The legal location for the Ute Tribal 31-04 is 770' FNL & 703' FWL NW/NW Sec. 31, T5S-R3W.
- (3) Attachment No. 2 is a map of the well. This map shows a circle with a ¼ mile radius centered on the Ute Tribal 31-04 well. The ¼ mile radius encompasses the area of review, AOR, within which Petroglyph is required to investigate all wells for mechanical integrity. The ¼ mile radius also identifies mineral ownership; those lands, and the the owners thereof, which must be provided notice of this application. The AOR has Ute Tribal 30-13, Ute Tribal 30-14N, and Ute Tribal 31-05 well(s) located in its ¼ mile radius.

- (4) Petroglyph proposes to utilize the Ute Tribal 31-04 as an injection well for enhanced recovery in the Antelope Creek Field.
- (5) Injection Zone The injection intervals are between 3456' and 5432' True Vertical Depth and located in the lower portion of the Green River Formation. The injection zone is confined within a 1976' section between the Green River "A" Lime marker bed and the top of the Basal Carbonate in the lower part of the formation. The injection zone is composed of lenticular calcareous sandstones interbedded with low permeable carbonates and calcareous shales. The lenticular sandstones vary in thickness from 1 to 30 feet.

Confining Zone – The overall confining strata above the injection zone consists of impermeable Green River calcareous shales and continuous beds of microcrystalline dolostone. The confining zone in the Ute Tribal 31-04 is 223 feet thick.

Attachment No. 3 is a structure map of the A-Marker surface.

Attachment No. 4 is a cross-section of the injection interval and confining zone.

(6) Enclosed as Attachment No. 5 are standard analyses of produced water from three batteries that currently serve as central handling facilities for all project producing wells. The analysis of the Green River formation water from the Ute Tribal 18-08 Satellite Battery is 12805 mg/L of total dissolved solids (TDS), Ute Tribal 21-11 Satellite Battery is 15659 mg/L TDS, and Ute Tribal 34-12-D3 Satellite Battery is 14590 mg/L TDS.

Injectate in the field is a mixture of produced water and fresh make-up water. The nearest injection well is the Ute Tribal 19-13, the most recent analysis of the water being injected into the Green River formation at this location is 7342 mg/L TDS. This analysis is also included in Attachment No. 5.

- (7) A summary of completion data from the Ute Tribal 31-04 and offset wells in the AOR are included in Attachment No. 6
- (8) The cement bond log is included in Attachment No. 7.
- (9) The open hole log for the Ute Tribal 31-04 is included in Attachment No. 8.

- (10) The Antelope Creek Field is operated under a Cooperative Plan of Development between the Ute Tribe and Petroglyph Energy. At the Ute Tribal 31-04 location, all mineral owners, surface owners and operators located within the AOR ¼ mile radius have been notified of the submitted EPA application to convert to injection. Attachment No. 9 is the Affidavit of Notification to all owners.
- (11) Petroglyph requests a maximum surface injection pressure of **1705**psi. The EPA Area Permit No. UT20736-00000 uses the formula:

Pm = (0.88psi/ft - 0.43psi/ft(Sg)) D

Where:

Pm = Maximum surface injection pressure

0.88psi/ft = Fracture gradient

D = Top perforation depth

0.43psi/ft = Hydrostatic pressure/hydraulic head


Sg = Specific gravity of injection fluid

For the Ute Tribal 31-04:


1705psi = (0.88psi/ft - 0.43(1.00)) 3789ft


- (12) Three wellbore diagrams for the Ute Tribal 31-04 are in Attachment No. 10. One diagram is for production, one for injection, and one for Plug & Abandonment (P&A).
- (13) The P&A procedure for this well is shown in Attachment No. 11.
- (14) Once the draft permit is issued, Petroglyph will conduct a Mechanical Integrity Test and a static bottom-hole pressure test. The MIT procedure is contained in Attachment No. 12. The conversion work will be satisfactorily completed and submitted to the EPA on Form 7520-12. A wellbore schematic will be included with this form.

- (15) Petroglyph will give proof of financial responsibility by posting a surety bond for the UIC well prior to final permit approval. A copy of this letter is contained in Attachment No. 13.
- (16) Petroglyph will install various gauges on the well so that the injection pressure and tubing/casing annulus pressure can be monitored. The well will be equipped with a flow meter with a cumulative volume recorder.



ATTACHMENT NO. 3: Map of the "A" Lime Marker





Ute Tribal 31-04 Well History

Well History:

Spud Well: 3/5/1998 Completed: 4/7/1998

First Production: 4/14/1998

Tops (KB):

BMSW* Found at 1264'

Green River 982'

A Marker 3456'

X Marker 3934'

Douglas Creek 4072'

B Limestone 4447'

Castle Peak 4945'

Basal Carbonate 5432'

Perf History

3/31/1998

B08.2	3800' to 3804'
C02	4013' to 4017'
C04	4108' to 4112'
C06	4267' to 4271'
C09.2	4397' to 4401'
D3	4506' to 4510'
E07	5310' to 5314'

Petroglyph Operating Co., Inc.
Ute Tribal #31-04
(770' FNL & 703' FWL)
NW NW Section 31, 5S-3W
Antelope Creek Field
Duchesne Co. Utah
API#: 43013320340000

*Plate 1 Utah Geological Survey Special Study 144. (2012). BMSW Elevation Contour Map, Uinta Basin, Utah. [map]. (CA 1:200,000) GL: 6254'

KB: 6264'

8 5/8" 24# Surface CSG @ 355' KB

cmt'd w/300 sx

Surface Hole size 12 1/4"

Cement top @ 170'

5 1/2" 15.5# J-55 CSG @ 5517'

cmt'd w/565sx

- Hole Size 7 7/8" bit

Perf's:

B08.2 3800' to 3804'

C02 4013' to 4017'

C04 4108' to 4112'

C06 4267' to 4271'

C09.2 4397' to 4401'


D3 4506' to 4510'

E07 5310' to 5314'


PBTD @ 5442' KB TD @ 5554' KB

(Not to Scale)

Ute Tribal 31-04 Injection



Ute Tribal 31-04 Plug and Abandonment





Production - Technical Review Worksheet

Permit No: <u>UT2</u>

. Well: UT 31-04

What Needs to be Done	Information Sources	Review & Evaluation Notes
Determine name, top and base of the confining zone(s) and the injection zone(s).	☐ Geologic data submitted☐ Well logs from area☐ ☐ Rublished a tister	Conf Zone: top3233 base 3456
, , , , , , , , , , , , , , , , , , , ,	☐ Published articles	Inj Zone: top 3456 base 5432 (Garden Guich 2-Marker) (top Wasatch)
Determine name, top and base of all USDWs. List base of lowermost USDW: Determine which USDWs are actually being used for water supply.	☐ Geologic data submitted ☐ nearby Water analyses ☐ nearby Well logs ☐ Water supply wells ☐ Published articles	Surface Elevation: 62 6254 KB 6264 Pub#92 base USDW: bgs: elev: submitted base USDW bgs: /264 elev: base of Uinta / top Green River: 982 KB 6264
Review and evaluate construction, casing and cementing records of proposed well.	☐ Data submitted ☐ Completion/workover reports ☐ Contractor invoices ☐ Logs: CBL, RTS, Temp, casing inspection, etc.	TD: 5554 PBTD: 5442 surface csg $8\frac{5}{8}2\frac{1}{4}$ ft $0-355$ sx long strg csg $5\frac{1}{8}^{2}1554$ ft $0-5517$ sx
Review and evaluate construction,	4-1: 1	TOC: submitted: /70 CBL: Wells in AOR: TD TOC CA 30-13 5584 SURF 31-05 5483 /565 30-14N 6347 SURF
casing and cementing records of AOR wells that penetrate injection zone.	good golo	
Review P&A plan for effective USDW protection, injection zone isolation and well closure.	☐ P&A plan ☐ Area geology	plug depths:
Review amount of FR - is it adequate to cover P&A costs of proposed in P&A plan?	☐ contractor bids / P&A cost histories ☐ nearby well P&A costs	FR instrument: Amount: \$
Calculate the maximum allowable injection pressure (MAIP).	☐ Fracture treatments ☐ Step Rate Test results ☐ Fracture gradient	top perforation: 3800 bottom perforation: 5314 injectate specific gravity: 101 Frac Gradient: - P8 psi initial MAIP = 1525 psi
Determine which logs and tests will be performed.		

Cement Bond Index (in millivolts - mV)

Date: September 2, 2015

Operator:

Petroglyph

Well:

Ute Tribal 31-04

Permit:

Enter the following values:

$$(in \ mV) = 60 \qquad m$$

Amplitude at 100% Bond (A-100) (in
$$mV$$
) =

Amplitude at
$$80\%$$
 Bond (A-80) = 2.3 _{mV}

 $[(0.2)\log A0 + (0.8)\log A100]$

 $[(0.1)\log A0 + (0.9)\log A100]$

 $3.4 \ mV$

 $[(0.3)\log A0 + (0.7)\log A100]$

Amplitude at 60% Bond (A-60)=

5.1 *mV*

 $[(0.4)\log A0 + (0.6)\log A100]$

Maximum Allowable Injection Pressure (MAIP) From Fracture Gradient

Date: 09/02/2015	Operator:	Petroglyph	
	Well:	Ute Tribal 31-04	
	Permit #:		

Enter the following values:

Specific Gravity of injectate =	1.010	g/cc
Depth to top of injection interval $=$	3,456	feet
Fracture Gradient $(FG) =$	0.880	psi/ft

$$MAIP = \underline{1,525}$$
 psig

(rounded down to nearest 5 psig)

where:

MSIP = [FG - (0.433 * SG)] * Depth to top of injection interval = 1529.868